








CROSS REFERENCE ACCESS DOOR

ACCESS DOORS (GP, UAD, BASIC, AL, GP LV, GP VIS, RP)








WBCA Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p>WBCA GP 100 Series</p>	<p>WBCA's number 1 specified door! General Purpose Premium, 14 ga. door, fully concealed offset hinge up to and including 24x24. Laser cut. Cam latch opens with screwdriver. Meets all architectural specifications.</p>	UF-5000	B-NT	NA	DW 16 GA	DSC-214M	TM	L-MPG	UA	3202 (M)	NT
 <p>WBCA UAD 200 Series</p>	<p>Utility, Meets most architectural specifications. 16 ga. steel. Trim 1-1/2" wide, Full length semi-concealed piano hinge. Laser cut. Cam latch opens with screwdriver.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WBCA BASIC 300 Series</p>	<p>The Contractor's Door. Our most Economical Door. 18 ga. steel (up to & including 16" x 16") and 16 ga. steel (18" x 18" - 24" x 24") Pin Lug hinge. Cam latch opens with screwdriver.</p>	NA	NA	AHD	NA	MC	NA	NA	NA	NA	NA
 <p>WBCA AL 1500 Aluminum Series</p>	<p>Lightweight, insulated. Concealed continuous piano type hinge, insulated with 1" TUFF-R polyisocyanurate. All aluminum.</p>	LT 4000	NA	PAL	NA	NA	NA	NA	NA	NA	NA
 <p>WBCA GP LV 100 Series</p>	<p>SPECIAL - with louvers. 14 ga. Steel door. Trim is 1-1/2" wide, Fully-concealed hinge up to and including 24 x 24. Laser cut. Available in WBCA UAD.</p>	NA	NA	AHD LOUVER	NA	NA	NA	NA	NA	NA	NA
 <p>WBCA GP VIS 100 Series</p>	<p>SPECIAL - Full glass in 14 ga. door, Fully-concealed hinge up to and including 24 x 24. Laser cut</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WBCA RP 110 Series</p>	<p>Removable Panel. Same quality features as the WBCA Premium door. For use in confined areas. Door is 14 ga. steel. Trim 1-1/2" wide. Laser cut. Cam latches opens with screwdriver.</p>	PA-3000	NA	NA	NA	WSR SERIES	NA	NA	NA	NA	NA



Distributed by
www.AccessDoor.com
 Phone: (800) 608-6568
 Fax: (409) 840-5545
 info@accessdoor.com

CROSS REFERENCE ACCESS DOOR








ACCESS DOORS (SMP, DW, RDW, PL, AP, AT, ATR)

WBCA Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 WBCA SMP 120 Series	Surface Mounted. 14 ga. steel. Trim 1-1/2" wide. Full length piano hinge allows door to open to 180°	SF-2000	NA	SFM	SF	DSC-214SM	NA	NA	MI-SF	NA	NA
 WBCA DW 400 Series	Drywall Bead. 14 ga. Steel, Frame is 16 ga. Steel, 1" wide perforated flange of 24 ga. galvanized steel for mounting purposes	DW-5040	AHD GYP	B-NP	DWB	KDW	WB	L-DWB	MDW	3023 (DW)	NM
 WBCA RDW 410 Series	Recessed-Drywall Bead. 14 ga. steel, 1" recessed depth accommodates drywall. Frame is 16 ga. Steel, 1" wide perforated flange of 24 ga. galvanized steel for mounting purposes.	DW-5015	B-NW	AHA GYP	NA	RDW	NA	L-DWR	CAD-DW	NA	RW
 WBCA PL 500 Series	Plaster Bead. 14 ga. Steel, Frame is 16 ga. Steel, 3" wide expanded flange 24 ga. galvanized material, space from the expanded flange to 1/4" safety edge will accommodate 1 3/4" of plaster	PS-5030	B-NP	AHD PLY	ML	DSC-214PL	PW	L-PSW	CAD-FL-PL	3200 K	NA
 "WBCA AP 510 Series	Recessed Plaster Bead. 14 ga. steel. Door is recessed 1" and lined with expanded metal lath. Frame is 16 ga. steel w/ 24 ga. galvanized casing bead and expanded metal lath surrounding door"	AP-5010	B-RP	AHA-PLY	AP	DSC-210PL	CP	L-APC	CAD-PL	3206 (AP)	RP
 WBCA AT 600 Series	Accoustical Tile (not available in drywall) 14. ga. steel. Door is recessed to accommodate up to 1" thick acoustical tile, Frame is 16 ga. Steel, Continuous piano hinge opens 180°	AT-5020	B-RA	AHA	AT	DSC-210	CT	L-CPA	CAD	3205 (AT)	RA
 WBCA ATR 610 Series	Fire-Resistive Ceiling for Accoustical Tile (not available in drywall) 16 ga. steel recessed 1-1/2", Frame is 16 ga. steel, hat channel type shape Continuous piano hinge allowing 180°	NA	NA	NA	CFR	KATR	NA	L-CPB	CAD-FR	3204 (ATR)	NA



Distributed by
www.AccessDoor.com
 Phone: (800) 608-6568
 Fax: (409) 840-5545
info@accessdoor.com










ACCESS DOORS (FR PRE, FR, FRU, FR DW, FR PL, FRB, FRC)

WBCA Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p>WBCA FR PRE 700 Series</p>	<p>Premium Heavy Duty. Fire-Rated/Walls Only 14 ga. steel. Inside door has rolled safety edges for protection, Frame is 16 ga. steel, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), between two pieces of 22 ga. steel, Continuous piano hinge allows opening to 180°</p>	NA	B-ST	NA	NA	NA	HGFD	NA	NA	NA	FST
 <p>WBCA FR 800 Series</p>	<p>Standard. Fire-Rated/Walls & Ceilings 18 ga. Steel, Frame is 16 ga. steel, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), in between two pieces of 22 ga. steel</p>	FW-5050	B-IT	PFI	FRC	KRP-150FR	FD	L-FRAP	MPFR	NA	IT
 <p>WBCA FRU 810 Series</p>	<p>Standard Ultra. Fire-Rated/Walls & Ceilings 18 ga. Steel, Frame is 16 ga. steel, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), in between two pieces of 22 ga. Steel, Fully concealed, pivot rod type hinge. Allows opening to 140°</p>	NA	NA	NA	NA	NA	NA	NA	NA	3218 (UFR)	NA
 <p>WBCA FR DW 820 Series</p>	<p>Fire-Rated/Walls & Ceilings Drywall Bead. 18 ga. steel, IFrame is 16 ga. steel, 1" wide perforated flange of 24 ga galvanized material for mounting purposes, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), between two pieces of 22 ga. steel</p>	NA	B-IW	PFI GYP	FRC-GB	KRP-350FR	FDWB	NA	MPFR-DW	NA	IW
 <p>WBCA FR PL 830 Series</p>	<p>Fire-Rated/Walls & Ceilings Plaster Bead. 18 ga. steel, Frame is 16 ga. steel, 3" wide perforated flange of 24 ga. galvanized material for mounting, space from expanded flange to 1/4" safety edge of door accommodates 1" plaster, 2 1/2" deep, Insulation: 2" thick mineral wool (ThermaFiber®), contained within door cavity</p>	NA	B-IP	NA	NA	NA	FDPW	NA	NA	NA	IP
 <p>WBCA FRB 900 Series</p>	<p>Fire-Rated/Walls Only Uninsulated 14 ga. steel. Fram is 16 ga. steel, 2 1/2" deep, Hinge is Continuous piano hinge. Allows opening to 180°. Latches are Self-latching direct action latch accepts both key and knurled knob"</p>	FB-5060	B-UT	PFN	FR	KRP-250FR	NA	NA	MFRU	NA	UT
 <p>WBCA FRC 50 Series</p>	<p>SPECIAL ONLY - Fire-Rated Ceiling 16 ga. steel recessed pan, Frame is 16 ga. steel, hat channel configuration, Insulation is 1/2" ceramic fiberboard, Hinge: Continuous piano hinge on long side of door, Latches are Self-latching, both key and knurled knob</p>	NA	NA	NA	NA	NA	NA	NA	NA	3210 (CFRAD)	NA



Distributed by
www.AccessDoor.com
 Phone: (800) 608-6568
 Fax: (409) 840-5545
 info@accessdoor.com


ACCESS DOORS (MD SEC, HG SEC, GY, TB, MAP, DUCT, EXT)

WBCA Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p>A special snake eye screwdriver is required to open this door</p> <p>WBCA MD SEC 1000 Series</p> 	<p>Medium Security Access Door 12 ga. steel door, 16 ga. steel frame, semi-concealed piano hinge. Counter sunk tamperproof screws, snake eye screwdriver is required. (not included)</p>	MS-7000	PSM	B-MT	SLK	DSB-123	SP	L-DPM	MI-SAD	3211-200	MT
 <p>Prepped for detention lock with paracentric key</p> <p>WBCA HG SEC 1100 Series</p> 	<p>High Security Access Door 10 ga. door, 2" x 2" x 3 1/16" angle frame, heavy duty butt hinges. Prepped for detention lock with paracentric key. (not included)</p>	SD-6000	PSH	B-HS	SLA	DSB-123-SD	HSP	L=DPH	MI-SADH	3211	HS
 <p>WBCA GY 3000 Series</p>	<p>Lightweight Gypsum Ceiling Panel Exceeds all required specifications that the market expects. 5/8" lightweight Gypsum drop-in-door.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WBCA TB 1200 Series</p>	<p>Drop-In Ceiling Access Door 16 ga. steel, continuous piano hinge, flush, stainless steel cam latch. Drops into the T-Bar ceiling grid. White baked enamel coat. Comes with mounting screws.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WBCA MAP Plastic</p>	<p>Reversible Access Door High impact ABS plastic. Door locked to return frame with snap friction catch, removable panel, tile-able.</p>	NA	NA	B-PL	NA	HA	NA	NA	PA	NA	PL
 <p>WBCA ADC/ADH 1400 Series</p>	<p>True Fit Duct Access Door 22 ga steel flanged frame, 22 ga steel door. ADH-D - continuous hinge, ADC-D - no hinge.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WBCA EXT 1300 Series</p>	<p>Uncomparable Exterior Access Door. 16 ga. steel door, trim 1-1/2" wide, 16 ga. steel frame, 2-3/8" depth Insulation: Double layer of 1" GreenGuard® Extruded Polystyrene insulation board, with R-Value @ 75°F Mean 5.0 x 2, FM approved.</p>	LT-4000	NA	B-XT	NA	MX	NA	L-XT	WID	NA	XT



Distributed by
www.AccessDoor.com
 Phone: (800) 608-6568
 Fax: (409) 840-5545
info@accessdoor.com

ACCESS DOORS (WIN)

WBCA Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p>WBCA WIN 1700 Series</p>	<p>Insulated Walk-In Duct Door 20 ga. galvanized steel door, 16 ga galvanized steel frame. 1" 3lb density insulation. 2 exterior latches with interior handles. 1/2" neoprene closed cell door to frame gasketing.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA



Distributed by
www.AccessDoor.com
 Phone: (800) 608-6568
 Fax: (409) 840-5545
 info@accessdoor.com